

Fetch All Campaigns Information

API: goGetAllCampaigns

Description

This endpoint provides a detailed list of all campaigns configured in the system, along with their properties and current status. The response includes essential information about each campaign, such as the name, dialing method, auto-dial level, and its activation status.

URL

https://**DOMAIN**.croco-dial.net/goAPIv2/goCampaigns/goAPI.php

Note: Replace `DOMAIN` with the specific domain you want to query.

Required Parameters

Parameter	Value	Description
goAction	goGetAllCampaigns	Action to retrieve all campaigns.

Parameter	Value	Description
goUser	MyUser	API authorized user.
goPass	MyPass	Password for the API authorized user.
responsetype	json/xml	Format of the response (<code>json</code> recommended).

Note: This endpoint uses body parameters for authentication instead of tokens or headers.

Request Examples:

GET:

```
curl -X GET "https://DOMAIN.croco-dial.net/goAPIv2/goCampaigns/goAPI.php?goAction=goGetAllCampaigns&goUser=MyUser&goPass=MyPass&responsetype=json"
```

POST (Form Data):

If you prefer to send the data as form parameters:

```
curl -X POST "https://DOMAIN.croco-dial.net/goAPIv2/goCampaigns/goAPI.php" \  
-H "Content-Type: application/x-www-form-urlencoded" \  
--data-urlencode "goAction=goGetAllCampaigns" \  
--data-urlencode "goUser=MyUser" \  
--data-urlencode "goPass=MyPass" \  
--data-urlencode "responsetype=json"
```

Example Response

```
{  
  "result": "success",
```

```
"data": {
  "rows": [
    {
      "id": "99999999",
      "campaign_name": "SERVERS",
      "dialer": "Y",
      "campaign_vdad_exten": "Y",
      "list_order_mix": "Y",
      "dial_method": "POWER DIAL",
      "auto_dial_level": "3",
      "active": "Y"
    },
    {
      "id": "88888888",
      "campaign_name": "DEFAULT",
      "dialer": "N",
      "campaign_vdad_exten": "Y",
      "list_order_mix": "Y",
      "dial_method": "POWER DIAL",
      "auto_dial_level": "0",
      "active": "Y"
    },
    {
      "id": "77777777",
      "campaign_name": "COLLECTIONS",
      "dialer": "Y",
      "campaign_vdad_exten": "Y",
      "list_order_mix": "Y",
      "dial_method": "POWER DIAL",
      "auto_dial_level": "2",
      "active": "Y"
    },
    ...
  ]
}
```

☐☐ Response Fields

Field	Description
id	Unique identifier of the campaign.
campaign_name	Name of the campaign.
dialer	Indicates if the campaign is configured for auto-dial (Y) or not (N).
campaign_vdad_exten	Defines if the campaign uses Answering Machine Detection (AMD).
list_order_mix	Indicates if the leads are mixed during the dialing process.
dial_method	The dialing method used: "POWER DIAL", "PREDICTIVE", or "PREVIEW".
auto_dial_level	Auto-dial level (number of channels per agent).
active	Specifies if the campaign is active (Y) or inactive (N).

Revision #1

Created 19 May 2025 15:39:32

Updated 19 March 2026 21:38:29