

Get Current Leads on Hopper by Campaign

API: getLeadsOnHopper

Description

This endpoint retrieves all leads currently in the hopper for a specific campaign. The hopper is a queue of leads that are ready to be dialed. The response includes detailed lead information such as loan ID, phone number, call disposition, source, list name, and an HTML button to delete the lead.

URL

https://**DOMAIN**.croco-dial.net/goAPIv2/goCampaigns/goAPI.php

Note: Replace `DOMAIN` with the specific domain you want to query.

Required Parameters

Parameter	Value	Description
-----------	-------	-------------

goAction	getLeadsOnHopper	Action to get the leads for a specific campaign.
goUser	MyUser	API authorized user.
goPass	MyPass	Password for the API authorized user.
campaign_id	ID-Campaign (number)	Campaign identifier to search hopper.
responsetype	json/xml	Format of the response (<code>json</code> recommended).

Note: This endpoint uses body parameters for authentication instead of tokens or headers.

Request Examples:

GET:

```
curl -X GET "https://DOMAIN.croco-dial.net/goAPIv2/goCampaigns/goAPI.php?goAction=getLeadsOnHopper&goUser=MyUser&goPass=MyPass&responsetype=json&campaign_id=123456"
```

POST (Form Data):

If you prefer to send the data as form parameters:

```
curl -X POST "https://DOMAIN.croco-dial.net/goAPIv2/goCampaigns/goAPI.php" \
-H "Content-Type: application/x-www-form-urlencoded" \
--data-urlencode "goAction=getLeadsOnHopper" \
--data-urlencode "goUser=MyUser" \
--data-urlencode "goPass=Mypass" \
--data-urlencode "campaign_id=123456" \
--data-urlencode "responsetype=json"
```

Example Response

```
{
  "result": "success",
  "data": {
    "rows": [
      {
        "lead_id": "10001",
        "last_local_call_time": "2025-06-01 14:23:45",
        "loan_id": "LN123456",
        "phone_number": "5551234567",
        "state": "CA",
        "disposition": "NEW",
        "count": 0,
        "gmt_offset_now": "-8.00",
        "hopper_id": "5001",
        "alt_dial": "MAIN",
        "list_name": "Default Leads List",
        "list_id": "901",
        "priority": 99,
        "source": "WEBFORM",
        "numrows": 2,
        "delete": "<button class=\\"btn btn-delete\\"><i class=\\"fa fa-trash\\" aria-hidden=\\"true\\"></i></button>"
      },
      {
        "lead_id": "10002",
        "last_local_call_time": "2025-06-01 13:12:09",
        "loan_id": "LN654321",
        "phone_number": "5559876543",
        "state": "TX",
        "disposition": "CALLBK",
        "count": 1,
        "gmt_offset_now": "-6.00",
        "hopper_id": "5002",
        "alt_dial": "ALT",
        "list_name": "Follow-up List",
        "list_id": "902",
        "priority": 90,
        "source": "IMPORT",
        "numrows": 2,
        "delete": "<button class=\\"btn btn-delete\\"><i class=\\"fa fa-trash\\" aria-hidden=\\"true\\"></i></button>"
      }
    ]
  }
}
```

```

    }
  ],
  "headers": [
    { "title": "Loan ID", "field": "loan_id" },
    { "title": "Phone Number", "field": "phone_number" },
    { "title": "Disposition", "field": "disposition" },
    { "title": "Count", "field": "count" },
    { "title": "Source", "field": "source" },
    { "title": "List Name", "field": "list_name" },
    { "title": "Lead ID", "field": "lead_id" },
    { "title": "Delete", "field": "delete", "formatter": "html" }
  ],
  "html": "<div class=\"toggleTitlesAction tabulator-Y3Yc\" style=\"width: 90%\">...</div>",
  "content": "table"
}
}

```

☐☐ Response Fields

Field Name	Description
<code>lead_id</code>	Unique identifier of the lead
<code>last_local_call_time</code>	Timestamp of the last local call to the lead (if any)
<code>loan_id</code>	Vendor lead code (often a unique external ID like a loan or case ID)
<code>phone_number</code>	Lead's phone number
<code>state</code>	US State (if available) from lead data
<code>disposition</code>	Status or outcome of the last interaction (e.g., <code>NEW</code> , <code>CALLBK</code> , <code>SALE</code>)
<code>count</code>	Number of times this lead has been called
<code>gmt_offset_now</code>	GMT offset of the lead's time zone

Field Name	Description
<code>hopper_id</code>	Internal hopper ID (queue ID)
<code>alt_dial</code>	Alternative dialing method or flag
<code>list_name</code>	Name of the list this lead belongs to
<code>list_id</code>	ID of the list
<code>priority</code>	Lead priority in the hopper
<code>source</code>	Source of the lead (e.g., <code>WEB</code> , <code>IMPORT</code>)
<code>numrows</code>	Total number of rows returned (same for all rows, used for frontend)
<code>delete</code>	HTML snippet for a delete button (used in frontend UI)

Revision #2
Created 2 June 2025 15:17:16
Updated 19 March 2026 21:38:29